



IMS-60

INTERPRETIVE MAP SERIES

**Landslide Hazard and Risk Study of
Eugene-Springfield and Lane County, Oregon**


By Nancy C. Calhoun, William J. Burns, Jon J. Franczyk,
and Gustavo Monteverde

Funding for this project was partially provided by the
Federal Emergency Management Agency (EMW-2015-CA-00106).


SHALLOW LANDSLIDE SUSCEPTIBILITY CLASSIFICATION

On the basis of several on- and post-studies (described in detail by Burns and Madin (2009)), a depth of 15 ft (4.5 m) is used to divide shallow from deep landslides. We prepared this shallow-susceptibility map by combining three factors: 1) calculated factor of safety (FOS), 2) landslide inventory data, and 3) buffers, as described below. We calculated the FOS by using conservative values such as baring the water table at the ground surface. We used landslide inventory data from the National Landslide Inventory (NLI) (1). The combinations of these factors comprise the relative susceptibility hazard zones: high, moderate, and low, as shown by the Susceptibility Hazard Zone Matrix below. The landslide susceptibility data are displayed on top of a base map that consists of the lidar-derived digital elevation model.

Each landslide susceptibility hazard zone shown on this map has been developed according to a number of specific factors. The classification scheme was developed by the Oregon Department of Geology and Mineral Industries (Burns and others, 2012). The symbology used to display these hazard zones is explained below.

 **HIGH:** High susceptibility to shallow

 MODERATE: Moderate susceptibility to shallow landslides

 **LOW:** Low susceptibility to shallow

① Factor of Safety (FOS)

$$\text{Factor of Safety} = \frac{\text{Resisting Forces}}{\text{Driving Forces}}$$

A slope with a FOS > 1 is theoretically a stable slope because the shear strength is greater than the shear stress. A slope with a FOS < 1 is theoretically an unstable slope because the shear stress is greater than the shear strength. A critically stable slope has a FOS = 1. Because of the inability to know all the conditions present within a slope, most geotechnical engineers and engineering geologists recommend that slopes with a FOS < 1.5 be considered potentially unstable (Turner and Schuster, 1996; Cornforth, 2005).

We calculated the FOS by using the infinite slope equation with conservative parameters. Saturated conditions were used so that a "worst case" scenario could be evaluated. Because of limitations related to a grid type analysis, we removed isolated areas with small (less than 4 ft [1.2 m] high) elevation

An inventory of all existing landslides in this area is shown on Plate 1. We prepared this inventory map by compiling all previously mapped landslides from published and unpublished geologic and landslide mapping, analyzing laser-based geomorphology and reviewing aerial photographs. We also attributed each landslide with classifications for activity, depth of failure, inventory type, and confidence of interpretation. We created the inventory by using the protocol developed by Burns and Madin (2009). We extracted the shallow landslides from the inventory and used these to create this shallow landslide susceptibility map.

Limitations include the following:

- 1) Every effort has been made to ensure the accuracy of the GIS and tabular databases, but it is not feasible to completely verify all of the original input data.

- 2) The shallow landslide susceptibility maps are based on three primary components: a) calculated factor of safety, b) landslide inventory, and c) buffers. Factors that can affect the level of detail and accuracy of the final susceptibility map include the following:

- a) Factor of safety calculations are strongly influenced by the accuracy and resolution of the input data for material properties, depth to failure surface, depth to groundwater, and slope angle. The first three of these inputs are usually estimates (material properties) or conservative limiting cases (depth to failure surface and groundwater), and local conditions may vary substantially from the estimated values used to make these maps.

- c) Infinite slope factor of safety calculations are done on one grid cell at a time without regard

- certain area. We developed buffers for areas with low factors of safety to counter the tendency to underestimate susceptibility. We developed the focal relief method to reduce the problem of overestimation of susceptibility due to steep slopes with low relief. However, overestimation and underestimation of susceptible areas are still likely in some isolated areas.
- 3) This susceptibility map is based on the topographic and landslide inventory data available as of the

- 4) The lidar-based digital elevation model does not distinguish elevation changes that may be due to the construction of structures like retaining walls. Because it would require extensive GIS and field work to locate all existing structures and remove them or adjust the material properties in the model, such features have been included as a conservative approach and must be examined on a site-specific basis.

- 5) Some landslides in the inventory may have been mitigated, thereby reducing their level of susceptibility. Because it is not feasible to collect detailed site-specific information on every landslide,

REFERENCES

- Burns, W.J., and Madin, J.P., 1999, Protocol for inventory mapping of landslide deposits from light detection and ranging (Lidar) imagery: Oregon Department of Geology and Mineral Industries Special Paper 42, 30 pp. geodatabase.state.or.us template.
- Burns, W.J., Madin, J.P., and Nickelson, K.A., 2012, Protocol for shallow-landslide susceptibility mapping: Oregon Department of Geology and Mineral Industries Special Paper 45, 32 p.
- Conforth, D.B., 2005, Landslides in practice: Investigation, analysis, and remedial/preventative options in soils: Hoboken, N.J., John Wiley and Sons, Inc., 596 p.
- Turner, A.K. and Schuster, R.L., eds., 1996, Landslides: investigation and mitigation. Washington, D.C., National Research Council, Transportation Research Board Special Report 247, 673 p.

Source Data:
Oregon LIDAR Consortium, 2008-2009 and 2013-2015, 3-foot bare earth lidar digital elevation model for Coberg (44123-B1), Creswell (43123-H1), Crow (43123-H3), Eugene East (44123-A1), Eugene West (44123-A2), Fox Hollow (43123-H2), Jasper (43122-H8), Junction City (44123-B2), Springfield (44123-A8), Walthersville (44122-A7).

Projection: Oregon Statewide Lambert Conformal Conic, Unit: International Feet
Horizontal Datum: NAD 1983
Vertical Datum: NAVD 83
Coordinate System: Zone 10N, NAD83

Software:

Cartography:

Water features are from the USGS National Hydrography Dataset (2015). Highways and signed roads are from the Oregon Department of Transportation (2013). Additional physical and cultural locations are from the Geographic Names Information System (GNIS), U.S. Geological Survey (2013). Eugene and Springfield community boundaries and building footprints are from Lane Council of Government (2017).

Map of the Eugene, Oregon area showing the study area for the 1990 census. The map includes labels for Eugene West, Eugene North, Eugene Southwest, Eugene South, Springfield West, and Springfield East. It also shows the city of Eugene, the city of Springfield, and the city of Lane County. The map includes a scale bar (0 to 10 miles and 0 to 10 kilometers) and a north arrow. The map is titled 'Map of the Eugene, Oregon area showing the study area for the 1990 census'.