

Distant Source (Alaska-Aleutian Subduction Zone) Tsunami Inundation Map

Newport South, Oregon

2013

Introduction

The Oregon Department of Geology and Mineral Industries (DOGAMI) has been identifying and mapping the tsunami inundation hazard along the Oregon coast since 1994. In 1994, DOGAMI manages the National Tsunami Hazard Mitigation Program, which has been administered by the National Oceanic and Atmospheric Administration (NOAA) since 1995. DOGAMI's work is designed to help cities, counties, and other areas in coastal areas reduce the potential for disastrous tsunami-related consequences by understanding and mitigating this geologic hazard. Using federal funding awarded by NOAA, DOGAMI has developed a new generation of tsunami inundation maps to help residents and visitors along the entire Oregon coast prepare for the next Cascadia Subduction Zone (CSZ) earthquake and tsunami, as well as for far-travelled, or "distant" tsunamis.

The "Ring of Fire," also called the Circum-Pacific belt, is the zone of earthquake activity surrounding the Pacific Ocean. It is an arc stretching from New Zealand along the eastern edge of Asia, north across the Aleutian Islands of Alaska, and south along the coast of North and South America (Figure 1). The Ring of Fire is located at the borders of the Pacific Plate and other major tectonic plates. The Pacific Plate is colliding with and sliding underneath other plates creating subduction zones that eventually release energy in the form of an earthquake rupture. This rupture causes a vertical displacement of water that creates a tsunami. When these events occur around the Ring of Fire but not directly off the Oregon coast, they take more time to travel the Pacific Ocean and arrive onshore in Oregon (Figure 2). Distant earthquake/tsunami events have affected the Oregon coast, for example, offshore Alaska in 1964 and offshore Japan in March 2011.

Historically, about 28 distant tsunamis have been documented by Oregon tide gauges since 1854. The most severe was generated by the 1964 M9.2 Prince William Sound earthquake in Alaska. Oregon was hit hard by the tsunami, which killed four people and caused an estimated \$20,000 to \$1 million dollars in damage to bridges, houses, cars, boats, and sea walls. The greatest tsunami damage in Oregon did not occur along the ocean front as one might expect, but in the estuary channels located further inland. Of the communities affected, Seaside was inundated by a 10 foot tsunami wave and was the hardest hit. Tsunami wave heights reached 10 to 11.5 feet in the Nehalem River, 10 to 11.5 feet at Coos Bay, 11.5 feet at Newport, 10 to 13 feet at Florence, 13 feet at Redwood, 13 feet at Brookings, and 14 feet at Coos Bay (Witter and others, 2011).

Alaska-Aleutian Model Specifications: DOGAMI modeled two distant earthquake and tsunami scenarios involving M9.2 earthquakes originating near the Gulf of Alaska. The first scenario attempts to replicate the 1964 Prince William Sound event, and the second scenario represents a hypothetical maximum event. This maximum event is the same model used by the U.S. Geological Survey (USGS) in their 2006 tsunami hazard assessment of Seaside (TPHA 2006). This model uses extreme fault model parameters that result in maximum seafloor uplift, nearly twice as large as in the 1964 earthquake. The selected source location on the Aleutian chain of islands also shows higher energy directed toward the Oregon coast than other Aleutian source locations. For these reasons the hypothetical "Alaska Maximum" scenario is selected as the worst case distant tsunami scenario for Oregon. Detailed information on fault geometry, subduction, computer models, and the methodology used to create the tsunami scenarios presented on this map can be found in DOGAMI Special Paper 43 (Witter and others, 2011).

Ring of Fire




Figure 1: The "Ring of Fire" is a zone of active earthquakes and volcanoes that rings much of the Pacific Ocean, including the Oregon coast. Volcanoes and earthquakes on this ring are caused by the movement of tectonic plates. One type of movement is called subduction — when one tectonic plate, such as those that compose the rock beneath the Pacific Ocean, sink beneath thicker, lighter plates that float up continental shelves. Earthquakes that occur as a result of subduction can trigger tsunamis.

Prince William Sound 1964 M9.2 Earthquake and Tsunami Travel Time Map




Figure 2: This image depicts the actual travel time of tsunami waves, in hours, around the Pacific Rim from the 1964 Prince William Sound earthquake. This magnitude 9.2 earthquake and resulting tsunami caused 125 deaths and \$2.1 billion in property loss. 684 deaths and 146 deaths in Alaska (NCEC/WDC). The tsunami generated many waves along the Gulf of Alaska, left serious damage in British Columbia, Hawaii, and along the west coast of the United States, and was recorded on tide gauges in Cuba and Puerto Rico.

Buildings within Tsunami Inundation Zones

	Entire Map Area	Newport	Unincorporated Areas
Total Buildings	2,333	1,480	853
Buildings within Tsunami Zones*			
Alaska M9.2 (1964)	43	22	23
Alaska Maximum	236	202	34
Percent of Buildings within Tsunami Zones			
Alaska M9.2 (1964)	1.9%	1.5%	2.5%
Alaska Maximum	10.2%	13.6%	4.1%

*Building counts shown are based on polygon centroids and are cumulative within the map area.




Figure 3: The table and chart show the number of buildings inundated for the Alaska M9.2 (1964) and the Alaska Maximum tsunami scenarios for cities and unincorporated portions of the map.

Estimated Tsunami Wave Height through Time for Simulated Gauge Station



Figure 4: This chart depicts the tsunami waves as they arrive at the selected reference point (simulated gauge station). It shows the change in wave heights for the two Alaska tsunami scenarios over an 8-hour period. Wave heights vary through time, and the first wave will not necessarily be the largest as waves interfere and reflect off local topography and bathymetry. Any dashed line indicates periods for which tsunami inundation has not yet reached or has receded from the station location and dry land is exposed.

Maximum Wave Elevation Profiles






Figure 5: These profiles depict the expected maximum tsunami wave elevation for the two Alaska tsunami scenarios along lines A-A' and B-B'. The tsunami scenarios are modeled to occur at a static (no flow) tide and equal to the Mean Higher High Water (MHHW) high tide.



Legend

- Earthquake Size
 - Alaska M9.2 (1964)
 - Alaska Maximum
- Slip / Deformation
 - Vertical seafloor deformation
 - Uniform slip on 3.2 subfaults with each assigned values ranging from 49 to 98 feet.
- Earthquake Magnitude
 - 9.2
 - 9.2
- Alaska Maximum Wet/Dry Zone
- Urban Growth Boundary
- Building Footprint
- Simulated Gauge Station
- Profile Location
- State Park
- Elevation Contour (25 ft intervals up to 200 ft)
- Fire Station
- Police Station
- School
- Hospital/Urgent Care Clinic
- U.S. Highway
- State Highway
- Improved Road

Tsunami Inundation Map Index




Data References

Source Data:
This map is based on hydrodynamic tsunami modeling by Joseph Zhang, Oregon Health and Science University, Portland, Oregon. Source data inputs were created by John T. English and George R. Priest, Department of Geology and Mineral Industries (DOGAMI), Portland, Oregon.
Hydrology data, contours, critical facilities, and building footprints were created by DOGAMI. Senate Bill 379 line data were digitized by Rachel L. Smith and Sean C. Palmer, DOGAMI, in 2011. GIS file: sb379.
Urban growth boundaries (2011) were provided by the Oregon Department of Land and Conservation and Development (DLCD).
Transportation data (2007) provided by Lincoln County were edited by DOGAMI to improve the spatial accuracy of the features or to add newly constructed roads not present in the original data layer.
Latitude data and time (DOGAMI) were downloaded from LDO 2011, 44123-89, Toledo South, LDO 2011, 44124-81, Newport South, and LDO 2011, 44124-82, Newport North, additional unpublished data from 2011.
Coordinate System: Oregon Statewide Lambert Conformal Conic, Unit: International Feet, Horizontal Datum: NAD 1983 HARN, Vertical Datum: NAVD 1983. Graticule shown with geographic coordinate (latitude/longitude).

References:
National Oceanic and Atmospheric Administration (NOAA) (2010). *Global Historical Tsunami Database*. Boulder, CO, USA. (http://www.ngdc.noaa.gov/hazard/tso_db.shtml)
Priest, G. R., 1995. Exploration of mapping methods and use of the National Tsunami Hazard Mitigation Program. Oregon Department of Geology and Mineral Industries Open-File Report O-95-07, 65 p.
English, J. T. and Priest, G. R., 2011. Simulating tsunami inundation hazards on the Oregon coast using hypothetical earthquake and tsunami scenarios. Oregon Department of Geology and Mineral Industries Special Paper 43, 31 p.
Witter, R. C., Zhang, Y., Wang, X., Priest, G. R., Goldfinger, C., Simons, L. L., English, J. T. and Priest, G. R., 2011. Simulating tsunami inundation hazards on the Oregon coast using hypothetical earthquake and tsunami scenarios. Oregon Department of Geology and Mineral Industries Special Paper 43, 31 p.
Map Production:
Cartographer: Rebecca L.B. Hughes, Sean C. Palmer
Editor: E. Witter
Reviewer: Vicki S. McConnell, Rachel L. Smith
Publisher: Deborah A. Schuller
Map Date: 02/08/2013

Software: ArcGIS® 10.1, Microsoft® Excel®, and Adobe® Illustrator®
Funding: This map was funded under award #NA408NA670014 by the National Oceanic and Atmospheric Administration (NOAA) through the National Tsunami Hazard Mitigation Program.
Map Data Creation/Development:
Tsunami Inundation Scenario: George R. Priest, Laura L. Simons, Daniel C. Lee, and Rachel L. Smith
Tsunami Inundation Scenario: Oregon Department of Geology and Mineral Industries
Bathymetry Data: Rebecca L.B. Hughes, Sean C. Palmer
Map Production:
Cartographer: Rebecca L.B. Hughes, Sean C. Palmer
Editor: E. Witter
Reviewer: Vicki S. McConnell, Rachel L. Smith
Publisher: Deborah A. Schuller
Map Date: 02/08/2013



For copies of this publication contact:
Oregon Department of Geology and Mineral Industries
600 NE Oregon Street, 6th, Ste. 950
Portland, Oregon 97232
Telephone (503) 676-2311
Fax (503) 676-2311