



The Oregon Department of Geology and Mineral Industries (DOGAMI) has been identifying and mapping the tsunami inundation hazard along the Oregon coast since 1994. In Oregon, DOGAMI manages the National Tsunami Hazard Mitigation Program, which has been administered by the National Oceanic and Atmospheric Administration (NOAA) since 1995. DOGAMI's work is designed to help cities, counties, and other sites in coastal areas reduce the potential for disastrous tsunami-related consequences by understanding and mitigating this geologic hazard. Using federal funding awarded by NOAA, DOGAMI has developed a new generation of tsunami inundation maps to help residents and visitors along the entire Oregon coast prepare for the next Cascadia Subduction Zone (CSZ) earthquake and tsunami as well as for far-travelled, or "distant" tsunamis.

Historically about 28 distant tsunamis have been documented by Oregon tide gauges since 1854. The most severe was generated by the 1914 M9.2 Prince William Sound earthquake in Alaska. Oregon was hit hard by the tsunami, which killed four people and caused an estimated 750,000 to 1 million dollars in damage to bridges, houses, cars, boats, and sea walls. The greatest tsunami damage in Oregon did not occur along the ocean front as one might expect, but in the estuary channels located further inland. Of the communities affected, Seaside was inundated by a 10 foot tsunami wave and was the hardest hit. Tsunami wave heights reached 10 to 11.5 feet in the Nehalem River, 10 to 11.5 feet at Depoe Bay, 11.5 feet at Newport, 10 to 11 feet at Florence, 11 feet at Reedsport, 11 feet at Brookings, and 14 feet at Coos Bay (Witter and others, 2011).

Alaska-Earthquake Model Specifications: DOGAMI modeled two distant earthquake and tsunami scenarios involving M9.2 earthquakes originating near the Gulf of Alaska. The first scenario attempts to replicate the 1964 Prince William Sound event, and the second scenario represents a hypothetical maximum event. This maximum event is the same model used by the US Geological Survey (USGS) in their 2006 tsunami hazard assessment of the Cascades (TPSWC 2006). This model uses extreme fault model parameters that result in maximum tsunami heights of 10 m for the 1964 earthquake. The 1964 earthquake selected source location on the Aleutian chain of islands also has the highest source directed toward the Oregon coast than other Alaska source locations. For these reasons the hypothetical Alaska "Maximum" scenario is selected as the worst case distant tsunami scenario for Oregon. Detailed information on fault geometries, subsidence, computer models, and the methodology used to create the tsunami scenarios presented on this map can be found in DOGAMI Special Paper 43 (Witter and others, 2011).

[illegible]

Figure 1: The "Ring of Fire" is a zone of active earthquakes and volcanoes that rings much of the Pacific Ocean, including the Oregon coast. Volcanoes and earthquakes on this ring are caused by the movements of tectonic plates. One type of movement is called subduction – when thin, oceanic plates, such as those that compose the rock beneath the Pacific Ocean, sink beneath thicker, lighter plates that make up continental plates. Earthquakes that occur as a result of subduction can trigger tsunamis.

Figure 2: This image depicts the actual initial tsunami arrival times, in hours, around the Pacific Rim from the 1964 Prince William Sound earthquake. This magnitude 9.2 earthquake and resulting tsunami caused 125 deaths and \$311 million in property loss, \$84 million and 106 deaths in Alaska (NGDC/AVDC). The tsunami devastated many towns along the Gulf of Alaska, left serious damage in British Columbia, Hawaii, and along the west coast of the United States, and was recorded on tide gauges in Cuba and Puerto Rico.

	Map Area	Unincorporated Areas
Total Buildings	542	542
Buildings within Tsunami Zones*		
Alaska MP 2 (1964)	0	0
Alaska Maximum	7	7
Percent of Buildings within Tsunami Zones		
Alaska MP 2 (1964)	0.0%	0.0%
Alaska Maximum	1.3%	1.3%

*Building counts shown are based on polygon centroids and are cumulative within the map area.

Figure 3: The table and chart show the number of buildings inundated for the Alaska M9.2 (1998) and the Alaska Maximum tsunami scenarios for cities and unincorporated portions of the map.

This tsunami inundation map displays the output of computer models representing the two selected tsunami scenarios: Alaska M9.2 (1964) and the Alaska Maximum. All tsunami simulations were run assuming that prevailing tide was static (no flow) and equal to Mean Higher High Water (MHHW) tide; MHHW is defined as the average height of the higher high tides observed over an 18-year period at the Garibaldi tide gauge. The map legend depicts the respective amounts of deformation and the earthquake magnitude for these two scenarios. Figure 3 shows the cumulative number of buildings inundated within the map area.

The computer simulation model output is provided to DOGAMI as millions of points with values that indicate whether the location of each point is wet or dry. These points are converted to wet and dry contour lines that form the extent of inundation. The transition area between the wet and dry contour lines is termed the *Wet/Dry Zone*, which equates to the amount of error in the model when determining the maximum inundation for the each scenario. Only the Alaska *Maximum Wet/Dry Zone* is shown on this map.

This map also shows the regulatory tsunami inundation line (Oregon Revised Statutes 455.446 and 455.447), commonly known as the Senate Bill 379 line. Senate Bill 379 (1995) instructed DOGAMI to establish the area of expected tsunami inundation based on scientific evidence and tsunami modeling in order to prohibit the construction of new essential and special occupancy structures in this tsunami inundation zone (Priest, 1995).

Time Series Scenario and Wave Elevation Profiles In addition to the time series graphics, the computer model produces time series data for "gauge" locations in the area. These points are simulated gauge stations that record the time, in seconds, of the tsunami wave arrival and the wave height observed. It is especially noteworthy that the greatest wave height and velocity observed are not necessarily associated with the first tsunami wave to arrive onshore. Therefore, evacuees should not assume that the tsunami event is over until the proper authorities have sounded the all-clear at the end of the evacuation. Figure 4 depicts the tsunami waves as they arrive at a simulated gauge location. Figure 5 depicts the overall wave height and inundation extent for the two scenarios at the profile locations shown on this map.

	Entire Map Area	Unincorporated Areas
Total Buildings	542	542
Buildings within Tsunami Zones*		
Alaska MR-2 (1964)	0	0
Alaska Maximum	7	7
Percent of Buildings within Tsunami Zones		
Alaska MR-2 (1964)	0.0%	0.0%
Alaska Maximum	1.3%	1.3%

*Building counts shown are based on polygon centroids and are cumulative within the map area.

Category	Alaska MR-2 (1964)	Alaska Maximum
Entire Map Area	0%	1.3%
Unincorporated Areas	0%	1.3%

Figure 3: The table and chart show the number of buildings inundated for the Alaska M9.2 (1998) and the Alaska Maximum tsunami scenarios for cities and unincorporated portions of the map.

The graph displays the elevation change in meters (m) on the y-axis (ranging from -20.0 to 80.0) against time in hours (h) on the x-axis (ranging from 0.0 to 8.0). Two data series are plotted: 'Alaska M9.2 (1964)' (orange line) and 'Alaska Maximum' (yellow line). Both series show a sharp increase in elevation starting around 3.5 hours, peaking at approximately 20 meters around 4.0 hours, and then fluctuating between 0 and 10 meters for the remainder of the 8-hour period. A legend box in the upper right corner identifies the series and includes a note: 'Change in water level for two tsunami scenarios at the simulated gauge station shown on the map'. A callout box points to the orange line, identifying it as 'Nectucca Bay Mouth - offshore (Station 45)'.

Time since Earthquake (hours)	Alaska M9.2 (1964) (m)	Alaska Maximum (m)
0.0	8.0	8.0
1.0	8.0	8.0
2.0	8.0	8.0
3.0	8.0	8.0
3.5	8.0	8.0
4.0	20.0	20.0
4.5	10.0	10.0
5.0	15.0	15.0
5.5	10.0	10.0
6.0	12.0	12.0
6.5	10.0	10.0
7.0	11.0	11.0
7.5	10.0	10.0
8.0	10.0	10.0

Figure 4: This chart depicts the tsunami waves as they arrive at the selected reference point (simulated gauge station). It shows the change in wave heights for the two Alaska tsunami scenarios over an 8-hour period. Wave heights vary through time, and the first wave will not necessarily be the largest as waves interfere and reflect off local topography and bathymetry.

A NECTUCCA BAY - NORTH **A'**

Elevation, feet (MW08)

200 ft
160 ft
120 ft
80 ft
40 ft
0 ft

0 mi 0.25 mi 0.5 mi 0.75 mi 1 mi

Distance along Profile, miles

Tsunami Scenarios

- Alaska M9.2 (1964)
- Alaska Maximum

Nectucca Bay

18 37% line

18 37% line

18 37% line

B NECTUCCA BAY - SOUTH **B'**

Elevation, feet (MW08)

200 ft
160 ft
120 ft
80 ft
40 ft
0 ft

0 mi 0.25 mi 0.5 mi

Distance along Profile, miles

Pacific Ocean

18 37% line

18 37% line

18 37% line

Figure 5: These profiles depict the expected maximum tsunami wave elevation for the two Alaska tsunami scenarios along lines A-A' and B-B'. The tsunami scenarios are modeled to occur at static (no flow) tide and equal to the Mean Higher High Water (MHHW) high tide.

[illegible]

Earthquake Type	Style / Deformation	Magnitude	Source Notes
Alaska M9.2 (1964)	Vertical seafloor deformation estimate	-9.2	This map is based on hydrographic (bathymetric) models developed by the U.S. Geological Survey and the National Oceanic and Atmospheric Administration (NOAA). The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office. The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office.
Alaska Maximum	Uniform slip on 12 subfaults with each assigned value ranging from 40 to 98 cm	-9.2	The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office. The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office.
Alaska Maximum Wet/Dry Zone			The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office. The map was prepared by the U.S. Geological Survey, Alaska Division, and the U.S. Geological Survey, Hawaiian Islands Office.
Urban Growth Boundary			Urban growth boundaries (UGBs) were provided by the Oregon Department of Land Conservation and Development (DLCD).
Building Footprint			Transportation data (11) provided by the Transportation Department of the Oregon Department of Transportation (DOT) were used to improve the spatial accuracy of the features or to build newly constructed roads not present in the original data source.
Streamlined Gauge Station			Users data are from Oregon State University (OSU) and the Oregon Department of Transportation (DOT).
Profil Location			Coordinates (Longitude, Latitude) were obtained from the National Oceanic and Atmospheric Administration (NOAA) and the U.S. Geological Survey (USGS).
Senate Bill 379 Line			Software used in this map includes ArcGIS 10.0, Microsoft Excel 2007, and Adobe Illustrator 9.0.
State Park			
Elevation Contour			

Data Sources

This map is based on hydrographic, tsunami modeling and bathymetric data from Oregon Health and Science University, Portland, Oregon. Data made input were created by the U.S. Geological Survey, Pacific Coastal Sciences Division, and Mineral Industries (DGC&M), Portland, Oregon.

Hydrology data: contours, critical facilities and buildings were portrayed by DGC&M. Series B1, B7 and B9 are the most detailed hydrologic data available. The data were collected by the U.S. Geological Survey, Pacific Coastal Sciences Division, and Mineral Industries (DGC&M), Portland, Oregon.

Tsunami data: In 2011 GIS file was sent, provided by Oregon Oceanic & Coastal Resources (2012).

Topographic data: 2011 provided by the Tliffmork County were edited by Oregon Department of Geology to improve the spatial accuracy of the features or to add new information.

User data: are from DGC&M, Lidar Data Quadrangles, LID0-2011-45123-87 H&B and LID0-2011-45122-86 H&B.

Coordinate System: Oregon Statewide Lambert Conformal Conic, Zone 1, North American Datum 1983, NAD 1983 HARN, Vertical datum: NAVD 1983 Gatchum used for geographic coordinates.

Software: ArcGIS® 10.0, Microsoft® Excel®, and Adobe® Illustrator®.

Funding: This map was funded under award #NA00RW546704 by the National Oceanic and Atmospheric Administration.

